

# SAFETY DATA SHEET

## VigorOx™ Oil & Gas Plus

SDS # : 79-21-0-26  
Revision date: 2019-03-11  
Format: NA  
Version 1.09



### 1. PRODUCT AND COMPANY IDENTIFICATION

#### Product Identifier

**Product Name** VigorOx™ Oil & Gas Plus  
**EPA Registration Number** 65402-8  
**CAS-No** 79-21-0  
**Synonyms** Peracetic Acid; Ethaneperoxoic Acid; Peroxyacetic Acid; Acetyl Hydroperoxide.

#### Recommended use of the chemical and restrictions on use

**Recommended Use:** Antimicrobial for use in oil-field and gas-field well operations  
**Restrictions on Use** Use as recommended by the label.

#### Manufacturer/Supplier

PeroxyChem LLC  
2005 Market Street  
Suite 3200  
Philadelphia, PA 19103  
Phone: +1 267/ 422-2400 (General Information)  
E-Mail: sdsinfo@peroxychem.com

#### Emergency telephone numbers

For leak, fire, spill or accident emergencies, call:  
1 800 / 424 9300 (CHEMTREC - U.S.A.)  
1 703 / 527 3887 (CHEMTREC - Collect - All Other Countries)  
1 303/ 389-1409 (Medical - U.S. - Call Collect)

### 2. HAZARDS IDENTIFICATION

#### Classification


#### **OSHA Regulatory Status**

This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Acute toxicity - Oral	Category 4
Acute toxicity - Dermal	Category 4
Acute toxicity - Inhalation (Vapors)	Category 4
Skin corrosion/irritation	Category 1 Sub-category B
Serious eye damage/eye irritation	Category 1
Specific target organ toxicity (single exposure)	Category 3

Organic Peroxide	Type F
Flammable liquids	Category 4
Corrosive to Metals	Category 1

**GHS Label elements, including precautionary statements****EMERGENCY OVERVIEW**

<p><b>Danger</b></p> <p><b>Hazard Statements</b></p> <p>H314 - Causes severe skin burns and eye damage  H302 - Harmful if swallowed  H312 - Harmful in contact with skin  H332 - Harmful if inhaled  H335 - May cause respiratory irritation  H242 - Heating may cause a fire  H227 - Combustible liquid  H290 - May be corrosive to metals</p> 
--

**Precautionary Statements - Prevention**

P280 - Wear protective gloves/ protective clothing/ eye protection/ face protection  
P260 - Do not breathe mist, vapours or spray.  
P220 - Keep/Store away from clothing/combustible materials  
P210 - Keep away from heat/sparks/open flames/hot surfaces. - No smoking  
P234 - Keep only in original container

**Precautionary Statements - Response**

P390 - Absorb spillage to prevent material damage  
P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
P310 - Immediately call a POISON CENTER or doctor  
P303 + P361 + P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower  
P363 - Wash contaminated clothing before reuse  
P304 + P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing  
P312 - Call a POISON CENTER or doctor if you feel unwell  
P301 + P330 + P331 - IF SWALLOWED: rinse mouth. Do NOT induce vomiting  
P370 + P378 - In case of fire: Use water for extinction

**Precautionary Statements - Storage**

P403 + P233 - Store in a well-ventilated place. Keep container tightly closed  
P411 + P235 - Store at temperatures not exceeding 50 °C/ 122 °F. Keep cool  
P410 - Protect from sunlight.

**Hazards not otherwise classified (HNOC)**

No hazards not otherwise classified were identified.

**Other Information****Supplemental Information**

Do not store on wooden pallets. Avoid damage to containers. In case of decomposition: isolate container, douse container with cool

water and dilute with large volumes of water. In case of leak or spill: Stop leak if this can be done without risk. Flush area with large quantities of water. Undiluted material should not be allowed to enter confined spaces. Risk of decomposition by heat or by contact with incompatible materials

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical name	CAS-No	Weight %
Water	7732-18-5	45
Hydrogen Peroxide	7722-84-1	23
Acetic Acid	64-19-7	16
Peracetic Acid	79-21-0	15
Sulfuric Acid	7664-93-9	1

### 4. FIRST AID MEASURES

<b>Eye Contact</b>	In case of eye contact, remove contact lenses and rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Call a physician immediately.
<b>Skin Contact</b>	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. Call a physician immediately.
<b>Inhalation</b>	Move to fresh air. If breathing difficulty or discomfort occurs and persists, obtain medical attention. If breathing is irregular or stopped, administer artificial respiration. Call a physician immediately.
<b>Ingestion</b>	Clean mouth with water and afterwards drink plenty of water. Do NOT induce vomiting. Call a physician or poison control center immediately.
<b>Most important symptoms and effects, both acute and delayed</b>	Liquid and mist are corrosive (causing burns); direct contact could cause irreversible damage to eyes including blindness and/or irreversible destruction of skin tissue. Vapor/mist will irritate nose, throat and lungs but will usually subside when exposure ceases.
<b>Indication of immediate medical attention and special treatment needed, if necessary</b>	This product can be corrosive to skin, eyes and mucous membranes. Consideration should be given to careful endoscopy as stomach or esophageal burns, perforations or strictures may occur. Careful gastric lavage with an endotracheal tube in place should be considered. Observation may be warranted. Treatment is controlled removal of exposure followed by symptomatic and supportive care.

### 5. FIRE-FIGHTING MEASURES

<b>Suitable Extinguishing Media</b>	Water. Cool containers with flooding quantities of water until well after fire is out.
<b>Unsuitable extinguishing media</b>	Chemical type extinguishers are not effective with peracetic acid or hydrogen peroxide.
<b>Specific Hazards Arising from the Chemical</b>	Decomposes under fire conditions to release oxygen that intensifies the fire.
<b>Explosion data</b>	
<b>Sensitivity to Mechanical Impact</b>	Not sensitive.
<b>Sensitivity to Static Discharge</b>	Not sensitive.
<b>Protective equipment and precautions for firefighters</b>	Fight fire from maximum distance or use unmanned hose holders or monitor nozzles. Wear self-contained breathing apparatus and protective suit.

**6. ACCIDENTAL RELEASE MEASURES**

<b>Personal Precautions</b>	Isolate and post spill area. Remove all sources of ignition. Wear suitable protective clothing, gloves and eye/face protection. For personal protection see Section 8.
<b>Other</b>	For further clean-up instructions, call PeroxyChem Emergency Hotline number listed in Section 1 "Product and Company Identification" above.
<b>Environmental Precautions</b>	Prevent material from entering into soil, ditches, sewers, waterways, and/or groundwater. See Section 12, Ecological Information for more detailed information.
<b>Methods for Containment</b>	Control runoff and isolate discharged material for proper disposal. Do not allow material to enter storm or sanitary sewer system.
<b>Methods for cleaning up</b>	Hydrogen peroxide is an ingredient in this product; completely submerge hydrogen peroxide contaminated clothing or other materials in water prior to drying. Residual hydrogen peroxide, if allowed to dry on combustible materials such as paper, fabrics, leather or wood can cause the material to ignite and result in a fire. Dispose of waste as indicated in Section 13.

**7. HANDLING AND STORAGE**

<b>Handling</b>	Handle product only in closed system or provide appropriate exhaust ventilation. Drums - Empty as thoroughly as possible. Triple rinse drums before disposal. Avoid contamination; impurities accelerate decomposition. Never return product to original container.
<b>Storage</b>	Store in original container. Do not stored near reducing agents, fuels or other non-compatible materials. Keep in a dry, cool and well-ventilated place. Keep away from direct sunlight. Keep away from heat and sources of ignition i.e., steam pipes, radiant heaters, hot air vents or welding sparks. Storage temperatures must not exceed product SADT or 50 ° C, whichever is lower. From a quality perspective, lower storage temperatures are recommended to maintain product assay. Use first in, first out storage system. Do not stack carboys more than two high, and NEVER double-stack pallets of carboys. Containers must be vented.
<b>Packaging material</b>	Do not store in metal containers.
<b>Incompatible products</b>	Oxidizing agents; Strong reducing agents; Combustible materials; Heavy metals

**8. EXPOSURE CONTROLS/PERSONAL PROTECTION****Control parameters****Exposure Guidelines**

Chemical name	ACGIH TLV	OSHA PEL	NIOSH	Mexico
Acetic Acid 64-19-7	STEL 15 ppm TWA: 10 ppm	TWA: 10 ppm TWA: 25 mg/m <sup>3</sup>	IDLH: 50 ppm TWA: 10 ppm TWA: 25 mg/m <sup>3</sup> STEL: 15 ppm STEL: 37 mg/m <sup>3</sup>	Mexico: TWA 10 ppm Mexico: TWA 25 mg/m <sup>3</sup> Mexico: STEL 15 ppm Mexico: STEL 37 mg/m <sup>3</sup>
Sulfuric Acid 7664-93-9	TWA: 0.2 mg/m <sup>3</sup>	TWA: 1 mg/m <sup>3</sup>	IDLH: 15 mg/m <sup>3</sup> TWA: 1 mg/m <sup>3</sup>	Mexico: TWA 1 mg/m <sup>3</sup>
Hydrogen Peroxide 7722-84-1	TWA: 1 ppm	TWA: 1 ppm TWA: 1.4 mg/m <sup>3</sup>	IDLH: 75 ppm TWA: 1 ppm TWA: 1.4 mg/m <sup>3</sup>	Mexico: TWA 1 ppm Mexico: TWA 1.5 mg/m <sup>3</sup> Mexico: STEL 2 ppm Mexico: STEL 3 mg/m <sup>3</sup>
Peracetic Acid 79-21-0	STEL 0.4 ppm	-	-	-

Chemical name	British Columbia	Quebec	Ontario TWAEV	Alberta
Acetic Acid 64-19-7	TWA: 10 ppm STEL: 15 ppm	TWA: 10 ppm TWA: 25 mg/m <sup>3</sup> STEL: 15 ppm STEL: 37 mg/m <sup>3</sup>	TWA: 10 ppm  STEL: 15 ppm	TWA: 10 ppm TWA: 25 mg/m <sup>3</sup> STEL: 15 ppm STEL: 37 mg/m <sup>3</sup>
Sulfuric Acid 7664-93-9	TWA: 0.2 mg/m <sup>3</sup>	TWA: 1 mg/m <sup>3</sup> STEL: 3 mg/m <sup>3</sup>	TWA: 0.2 mg/m <sup>3</sup> thoracic	TWA: 1 mg/m <sup>3</sup> STEL: 3 mg/m <sup>3</sup>
Hydrogen Peroxide 7722-84-1	TWA: 1 ppm	TWA: 1 ppm TWA: 1.4 mg/m <sup>3</sup>	TWA: 1 ppm	TWA: 1 ppm TWA: 1.4 mg/m <sup>3</sup>

**Appropriate engineering controls**

**Engineering measures** Apply technical measures to comply with the occupational exposure limits. When working in confined spaces (tanks, containers, etc.), ensure that there is a supply of air suitable for breathing and wear the recommended equipment.

**Individual protection measures, such as personal protective equipment**

**Eye/Face Protection** Tightly fitting safety goggles. Face-shield.

**Skin and Body Protection** Rubber or neoprene footwear. Impervious clothing materials such as rubber, neoprene, nitrile or polyvinyl chloride. Wear liquid proof rubber or neoprene gloves. Hydrogen peroxide is an ingredient in this product; completely submerge hydrogen peroxide contaminated clothing or other materials in water prior to drying. Residual hydrogen peroxide, if allowed to dry on combustible materials such as paper, fabrics, leather or wood can cause the material to ignite and result in a fire.

**Hand Protection** Rubber/latex/neoprene or other suitable chemical resistant gloves. Wash the outside of gloves with soap and water prior to removal. Inspect regularly for leaks.

**Respiratory Protection** If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.

**Hygiene measures** Clean water should be available for washing in case of eye or skin contamination. Remove and wash contaminated clothing before re-use. Do not eat, drink or smoke when using this product.

**General information** Protective engineering solutions should be implemented and in use before personal protective equipment is considered.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

**Information on basic physical and chemical properties**

**Appearance** Clear, colorless liquid  
**Physical State** Liquid  
**Color** Colorless  
**Odor** stinging, Pungent, vinegar-like  
**Odor threshold** No information available  
**pH** < 1.0 @ 20 °C  
 2.78 @ 20 °C (1% solution)  
**Melting point/freezing point** -49 °C / -56 °F  
**Boiling Point/Range** 108 °C / 226 °F (with decomposition)  
**Flash point** Closed cup: 68 °C  
 Open Cup: No measurable flash point up to 100° C  
**Evaporation Rate** Fire Point: No fire point. This material will not sustain a flame  
 > 1.0 (n-butyl acetate=1)

<b>Flammability (solid, gas)</b>	Substance does not burn but will support combustion
<b>Flammability Limit in Air</b>	
<b>Upper flammability limit:</b>	No information available
<b>Lower flammability limit:</b>	No information available
<b>Vapor pressure</b>	22 mm Hg @ 20°C (68°F)
<b>Vapor density</b>	No information available
<b>Density</b>	9.7 lb/gal @ 25 °C
<b>Specific gravity</b>	1.16 @ 25 °C
<b>Water solubility</b>	completely soluble
<b>Solubility in other solvents</b>	No information available
<b>Partition coefficient</b>	log Pow = -0.52 @ 25 °C
<b>Autoignition temperature</b>	251 - 254 °C
<b>Decomposition temperature</b>	> 55 °C (SADT)
<b>Viscosity, kinematic</b>	No information available
<b>Viscosity, dynamic</b>	No information available
<b>Explosive properties</b>	No information available
<b>Oxidizing properties</b>	Strong oxidizer
<b>Molecular weight</b>	No information available
<b>Bulk density</b>	Not applicable

## 10. STABILITY AND REACTIVITY

<b>Reactivity</b>	Reactive and oxidizing agent. Organic peroxide. .
<b>Chemical Stability</b>	Stable under recommended storage conditions. Contamination or heat could initiate decomposition.
<b>Possibility of Hazardous Reactions</b>	May produce explosive reactions with Acetic Anhydride.
<b>Hazardous polymerization</b>	Hazardous polymerization does not occur.
<b>Conditions to avoid</b>	Heat, flames and sparks. Temperatures above 50°C or SADT, whichever is lower.
<b>Incompatible materials</b>	Strong reducing agents; Combustible materials; Heavy metals.
	Oxidizing agents;
<b>Hazardous Decomposition Products</b>	Acetic acid and oxygen that supports combustion.

## 11. TOXICOLOGICAL INFORMATION

### Product Information

<b>LD50 Oral</b>	LD50 Rat = 50 -500 mg/kg/bw (35% Peracetic acid) LD50 rat = 1026-1780 mg/kg/bw (15% Peracetic acid) LD50 rat = 185-3622 mg/kg/bw (2.6-6.11% Peracetic acid)
<b>LD50 Dermal</b>	LD50 Rat = 1957 mg/kg/bw (15% Peracetic acid) LD50 rat = 1147 mg/kg/bw (5% Peracetic acid) LD50 rat = >2000 mg/kg/bw (Peracetic acid 0.15%-0.89%)
<b>LC50 Inhalation</b>	LC50 (4-hr) Rat = 4080 mg/m <sup>3</sup> (5% Peracetic acid) (aerosol)
<b>Serious eye damage/eye irritation</b>	Corrosive. Risk of serious damage to eyes.
<b>Skin corrosion/irritation</b>	Corrosive to skin. Severely irritating (rabbit).
<b>Sensitization</b>	Did not cause sensitization on laboratory animals.

**Information on toxicological effects**

**Symptoms** Liquid and mist are corrosive and can cause burns, direct contact could cause irreversible damage to eyes including blindness and/or irreversible destruction of skin tissue. Vapor/mist will irritate the nose, throat and lungs, but will usually subside when exposure ceases. The severity of the effects depends in the concentration and dose.

**Delayed and immediate effects as well as chronic effects from short and long-term exposure**

**Chronic toxicity** Repeated inhalation of the mist may cause inflammation of the upper respiratory tract, chronic bronchitis and etching of the dental enamel.

**Carcinogenicity** Did not show carcinogenic effects in animal experiments. Topical applications do not produce skin tumors. Not recognized as carcinogenic by Research Agencies (IARC, NTP, OSHA, ACGIH).

**Mutagenicity** This product is not recognized as mutagenic by Research Agencies. Did not show mutagenic effects in animal experiments.

**Reproductive toxicity** This product is not recognized as reprotox by Research Agencies. No toxicity to reproduction in animal studies.

**STOT - single exposure** May cause respiratory irritation.  
**STOT - repeated exposure** Not classified.

**Aspiration hazard** No information available.

## 12. ECOLOGICAL INFORMATION

**Ecotoxicity**

**Ecotoxicity effects** Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment

<b>Peracetic Acid (79-21-0)</b>				
Active Ingredient(s)	Duration	Species	Value	Units
Peracetic Acid 15%	96 h LC50	Oncorhynchus mykiss (rainbow trout)	0.53	mg/L
Peracetic Acid 5%	96 h LC50	Bluegill sunfish	1.1	mg/L
Peracetic Acid	33 d NOEC	Brachydanio rerio	0.00225	mg/L
Peracetic Acid 5%	96 h LC50	Oncorhynchus mykiss (rainbow trout)	1.6	mg/L
Peracetic Acid 5%	48 h EC50	Daphnia magna	0.73	mg/L
Peracetic Acid 12.5%	48 h EC50	Mytilus sduilis	0.27	mg/L
Peracetic Acid 15%	21 d NOEC	Daphnia magna	0.05	mg/L
Peracetic Acid 5%	72 h EC50	Selenastrum capricornutum	0.16	mg/L
Peracetic Acid 5%	120 h EC50	Selenastrum capricornutum	0.18	mg/L
Peracetic Acid 5%	72 h NOEC	Selenastrum capricornutum	0.061	mg/L
Peracetic Acid	3 h EC50	Respiration inhibition test (OECD 209)	5.1	mg/L

<b>Persistence and degradability</b>	Peracetic acid is completely miscible with water. Aqueous solutions of peracetic acid hydrolyze to acetic acid and hydrogen peroxide. Product is biodegradable.
<b>Bioaccumulation</b>	Based on its low octanol-water partition coefficient and its rapid degradation in the environment, this product is not bioaccumuable.
<b>Mobility</b>	Peracetic acid released in the environment will partition almost exclusively (>99%) to the water compartment. Only a minor part (<1%) will remain in the atmosphere, where it is expected to undergo rapid decomposition with a half life of 22 minutes. The fate of peracetic acid in the environment is mainly determined by its degradation.
<b>Other Adverse Effects</b>	None known.

### 13. DISPOSAL CONSIDERATIONS

<b>Waste disposal methods</b>	This material, as supplied, is a hazardous waste according to federal regulations (40 CFR 261). If these wastes cannot be disposed of by use according to label instructions, contact appropriate disposal authorities for guidance.
<b>US EPA Waste Number</b>	D001; D002.
<b>Contaminated Packaging</b>	Do not rinse returnable containers or receptacles not intended for other uses. Non-returnable containers that held this material should be cleaned by triple-rinsing prior to recycle or disposal. Dispose of in accordance with local regulations. Empty remaining contents. Clean container with water.

### 14. TRANSPORT INFORMATION

#### DOT

<b>UN/ID no</b>	UN3109
<b>Proper Shipping Name</b>	ORGANIC PEROXIDE TYPE F, LIQUID (<=17% Peracetic Acid with <=26% Hydrogen Peroxide)
<b>Hazard class</b>	5.2
<b>Subsidiary class</b>	8
<b>Reportable Quantity (RQ)</b>	Hazardous Substance/RQ: Not applicable

#### TDG

<b>UN/ID no</b>	UN3109
<b>Proper Shipping Name</b>	ORGANIC PEROXIDE TYPE F, LIQUID (<=17% Peracetic Acid with <=26% Hydrogen Peroxide)
<b>Hazard class</b>	5.2
<b>Subsidiary class</b>	8
<b>Packing Group</b>	II

#### ICAO/IATA

Air regulation permit shipment of peracetic acid in non-vented containers for Air Cargo Only aircraft, as well as for Passenger and Cargo aircraft. HOWEVER, all peracetic acid containers are vented and therefore, air shipments of peracetic acid are not permitted. IATA air regulations state that venting of packages containing oxidizing substances is not permitted for air transport.

#### IMDG/IMO

<b>UN/ID no</b>	UN3109
<b>Proper Shipping Name</b>	ORGANIC PEROXIDE TYPE F, LIQUID (<=17% Peracetic Acid with <=26% Hydrogen Peroxide)
<b>Hazard class</b>	5.2
<b>Subsidiary Hazard Class</b>	8
<b>Marine Pollutant</b>	When shipped by vessel, this material meets the definition of an environmentally hazardous substance.



**OTHER INFORMATION**

Protect from physical damage. Material is shipped in 5 gal. (45 lb.), 30 gal. (250 lb.) and 55 gal. (495 lb.) vented linear (not cross-linked) polyethylene containers, as well as linear (not cross-linked) polyethylene IBC's (330 gal.). Do not ship on wooden pallets.

**15. REGULATORY INFORMATION****U.S. Federal Regulations****Clean Air Act (CAA) - Accidental Release Prevention**

Peracetic acid is listed as a Regulated Toxic Substance at 40 CFR 68.130. Pursuant to the threshold determination provisions for mixtures at 40 CFR 68.155(b)(1), the partial pressure of peracetic acid in VigorOx products (up to 35% solutions) are less than 10 mm Hg at 25°C, and thus the product, as sold, is not subject to the threshold determination under the Risk Management Planning regulations

**SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372:

Chemical name	CAS-No	Weight %	SARA 313 - Threshold Values %
Sulfuric Acid - 7664-93-9	7664-93-9	1	1.0
Peracetic Acid - 79-21-0	79-21-0	15	1.0

**SARA 311/312 Hazard Categories**

This product has the following hazards that are reportable under The Emergency Planning and Community Right-to-Know rule (EPCRA Tier II):

- Flammable/combustible material
- Organic Peroxide
- Corrosive to Metals
- Acute toxicity
- Serious eye damage/eye irritation
- Skin corrosion/irritation
- Specific Target Organ Toxicity (STOT) - Single Exposure

**Clean Water Act**

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42):

Chemical name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Acetic Acid 64-19-7	5000 lb			X
Sulfuric Acid 7664-93-9	1000 lb			X

**CERCLA/EPCRA**

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Response Compensation and Liability Act (CERCLA) or as an extremely hazardous substance (EHS) under the Emergency Planning and Community Right to Know Act (EPCRA) / Superfund Amendments and Reauthorization Act (SARA).

Chemical name	CERCLA Hazardous Substances RQs (40 CFR 302.4)	SARA Sec 304 Extremely Hazardous Substance RQ (40 CFR 355 Appendix A)	SARA Section 302 EHS Threshold Planning Quantity (40 CFR 355)
Hydrogen Peroxide 7722-84-1		1000 lb	1000 lb
Acetic Acid 64-19-7	5000 lb		
Peracetic Acid 79-21-0		500 lb	500 lb

## VigorOx™ Oil & Gas Plus

SDS #: 79-21-0-26  
Revision date: 2019-03-11  
Version 1.09

Chemical name	CERCLA Hazardous Substances RQs (40 CFR 302.4)	SARA Sec 304 Extremely Hazardous Substance RQ (40 CFR 355 Appendix A)	SARA Section 302 EHS Threshold Planning Quantity (40 CFR 355)
Sulfuric Acid 7664-93-9	1000 lb	1000 lb	1000 lb

Hydrogen Peroxide RQ is for concentrations of > 52% only

### FIFRA INFORMATION

**EPA Registration Number** 65402-8

*This chemical is a pesticide product registered by the United States Environmental Protection Agency and is subject to certain labeling requirements under federal pesticide law. These requirements differ from the classification criteria and hazard information required for safety data sheets (SDS), and for workplace labels of non-pesticide chemicals. The hazard information required on the pesticide label is reproduced below. The pesticide label also includes other important information, including directions for use.*

#### **DANGER**

*Corrosive, causes irreversible eye damage and skin burns. May be fatal if inhaled. Harmful if swallowed or absorbed through skin. Strong oxidizing agent. This pesticide is toxic to birds, mammals, fish and aquatic invertebrates.*

### US State Regulations

#### **U.S. State Right-to-Know Regulations**

This product contains the following substances regulated under state Right-to-Know laws:

Chemical name	Massachusetts	New Jersey	Pennsylvania	Illinois	Rhode Island
Hydrogen Peroxide	X	X	X		
Acetic Acid	X	X	X		X
Peracetic Acid	X	X	X	X	X
Sulfuric Acid	X	X	X	X	X

#### **California Proposition 65**

This product does not contain any Proposition 65 chemicals

### CANADA

#### **Environmental Emergencies**

Chemical name	Canada - Environmental Emergencies - Part 1 Substances - Substances Likely to Explode - Minimum Threshold Quantities	Canada - Environmental Emergencies - Part 1 Substances - Substances Likely to Explode - Minimum Mixture Concentrations	Canada - Environmental Emergencies - Part 2 Substances - Substances Hazardous When Inhaled - Minimum Threshold Quantities	Canada - Environmental Emergencies - Part 2 Substances - Substances Hazardous When Inhaled - Minimum Mixture Concentrations
Hydrogen Peroxide 7722-84-1	3.40 tonnes Minimum quantity	52		
Acetic Acid 64-19-7			6.80 tonnes Minimum quantity	95
Peracetic Acid 79-21-0			4.50 tonnes Minimum quantity	10

Note: Peracetic acid is exempt from Environmental Emergency Regulations SOR/2003-307 requirements per List of Substances Section 2(b) as it is a component of a mixture and its partial pressure in the mixture is less than 10 mm Hg. In addition the concentrations of the Hydrogen Peroxide and Acetic Acid in the mixture are below their minimum concentrations.

#### **Canadian National Pollutant Release Inventory**

Chemical name	Canada - 2017 NPRI (National Pollutant Release Inventory)
Acetic Acid 64-19-7	Part 4 Substance

Peracetic Acid 79-21-0	Part 1, Group A Substance
Sulfuric Acid 7664-93-9	Part 1, Group A Substance

**International Inventories**

Chemical name	TSCA (United States)	DSL (Canada)	EINECS/EL INCS (Europe)	ENCS (Japan)	China (IECSC)	KECL (Korea)	PICCS (Philippines)	AICS (Australia)	NZIoC (New Zealand)
Hydrogen Peroxide 7722-84-1	X	X	X	X	X	X	X	X	X
Acetic Acid 64-19-7	X	X	X	X	X	X	X	X	X
Peracetic Acid 79-21-0	X	X	X	X	X	X	X	X	X
Sulfuric Acid 7664-93-9	X	X	X	X	X	X	X	X	X

All ingredients are directly listed on the active TSCA Inventory

**Mexico**

Mexico - Grade

Moderate risk, Grade 2

<b>16. OTHER INFORMATION</b>
------------------------------

<b>NFPA</b>	<b>Health Hazards</b> 3	<b>Flammability</b> 1	<b>Stability</b> 2	<b>Special Hazards</b> OX
<b>HMIS</b>	<b>Health Hazards</b> 3	<b>Flammability</b> 1	<b>Physical hazard</b> 2	<b>Special precautions</b> H

**NFPA/HMIS Ratings Legend**

Severe = 4; Serious = 3; Moderate = 2; Slight = 1; Minimal = 0

Special Hazards: OX = Oxidizer. Protection = H (Safety goggles, gloves, apron, the use of supplied air or SCBA respirator is required in lieu of a vapor cartridge respirator)

**Uniform Fire Code**

Organic Peroxide: Class 4--Liquid

**Revision date:**

2019-03-11

**Revision note**

SDS sections updated: 2, 7, 15.

**Disclaimer**

PeroxyChem believes that the information and recommendations contained herein (including data and statements) are accurate as of the date hereof. NO WARRANTY OF FITNESS FOR ANY PARTICULAR PURPOSE, WARRANTY OF MERCHANTABILITY OR ANY OTHER WARRANTY, EXPRESSED OR IMPLIED, IS MADE CONCERNING THE INFORMATION PROVIDED HEREIN. The information provided herein relates only to the specified product designated and may not be applicable where such product is used in combination with any other materials or in any process. Further, since the conditions and methods of use are beyond the control of PeroxyChem, PeroxyChem expressly disclaims any and all liability as to any results obtained or arising from any use of the products or reliance on such information.

**Prepared By:**

PeroxyChem  
VigorOx - Trademark of Peroxychem  
© 2019 PeroxyChem. All Rights Reserved.  
**End of Safety Data Sheet**